## Smoke & CO Detectors

## SMOKE DETECTOR REQUIREMENTS

R314.2.3 During construction. Pursuant to section 29-315b of the Connecticut General Statutes, whenever a dwelling is

occupied during interior alterations or additions requiring a building permit, the temporary installation of battery-operated smoke alarms shall be required in the vicinity of such alterations or additions for the duration of construction activities. A combined smoke and carbon monoxide alarm may be installed to comply with R315.2.3 and this section.

R314.2.2 Alterations, repairs, and additions. When alterations, repairs or additions requiring a permit occur, or when one or more sleeping rooms are added or created in existing dwellings, the entire dwelling unit shall be provided with

smoke alarms located as required for new dwellings.

Exceptions:

1. Work involving the exterior surfaces of dwellings, such as the replacement of roofing or Siding, or the

addition or replacement of windows or doors, or the addition of a porch or decks, are exempt from the requirements of this section.

2. Installation, alteration, or repairs of plumbing, mechanical or electrical systems are exempt from the requirements of this section.

R314.3 Location. Smoke alarms shall be installed in the following locations:

1. In each sleeping room.

2. Outside each separate sleeping area in the immediate vicinity of the bedrooms.

3. On each additional story of the dwelling, including basements and habitable attics and not including crawlspaces and uninhabitable attics. In dwellings or dwelling units with split levels and without an intervening door between the adjacent levels, a smoke alarm installed on the upper level shall suffice for the adjacent lower level provided that the lower level is less than one full story below the upper level.

4. Not less than 3 feet (914 mm) horizontally from the door or opening of a bathroom that contains a bathtub or shower unless this would prevent placement of a smoke alarm required by this section. 5. In the hallway and in the room open to the hallway in dwelling units where the ceiling height of a room open to a hallway serving bedrooms exceeds that of the hallway by 24 inches (610 mm) or more.

Continued...

## CO DETECTOR REQUIREMENTS

R315.2.3 During construction. Pursuant to section 29-315b of the Connecticut General Statutes, whenever a dwelling is occupied during interior alterations or additions requiring a building permit where a fuel-burning appliance, fireplace or

attached garage exists, the temporary installation of battery-operated carbon monoxide alarms shall be required in the

vicinity of such alterations or additions for the duration of construction activities. A combined smoke and carbon

monoxide alarm may be installed to comply with R314.2.3 and this section.

R315.2.2 Alterations, repairs, and additions. Where alterations, repairs or additions requiring a permit occur, or where one or more sleeping rooms are added or created in existing dwellings, the individual dwelling unit shall be equipped with

carbon monoxide alarms located as required for new dwellings.

Exceptions:

1. Work involving the exterior surfaces of dwellings, such as the replacement of roofing or siding, or the addition

or replacement of windows or doors, or the addition of a porch or deck.

2. Installation, alteration or repairs of plumbing systems.

3. Installation, alteration or repairs of mechanical systems that are not fuel fired.

R315.3 Location. Carbon monoxide alarms in dwelling units shall be installed outside of each separate sleeping area in

the immediate vicinity of the bedrooms and on each additional habitable level of the dwelling unit. Where a fuel-burning

appliance is located within a bedroom or its attached bathroom, a carbon monoxide alarm shall be installed within the

bedroom. The alarm shall be clearly audible in all bedrooms over background noise levels with all intervening doors closed.